

ALTDORF GLACIER 424

Chemwatch Material Safety Data Sheet

Issue Date: 01 Sept 2021 CHEMWATCH 16-3657

NC317ECP Version No:2.0

CD 2008/2 Page 1 of 11

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

ALTDORF GLACIER 424

PRODUCT USE

Soluble cutting oil.

SUPPLIER

Company: Wolfmach

Address:

46 Wilson Street

Wanganui

New Zealand

Telephone: +64 6 349 6212

Fax: +64 6 347 2069

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

None

RISK

None under normal operating conditions.

SAFETY

Safety Codes Safety Phrases

S23 Do not breathe gas/ fumes/ vapour/ spray.

S39 Wear eye/ face protection.

S51 Use only in well ventilated areas.

S09 Keep container in a well ventilated place.

S07 Keep container tightly closed.

S27 Take off immediately all contaminated clothing.

S26 In case of contact with eyes rinse with plenty of water and contact Doctor or Poisons Information Centre.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME CAS RN %

paraffinic distillate, heavy, solvent- dewaxed (severe) 64742-65-0. 70-90

other non-hazardous ingredients <30

continued...

ALTDORF GLACIER 424

Chemwatch Material Safety Data Sheet

Issue Date: 01 Sept 2021 CHEMWATCH 16-3657

NC317ECP Version No:2.0

CD 2008/2 Page 2 of 11

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
 - If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
 - Observe the patient carefully.
 - Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
 - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
 - Seek medical advice.
- Avoid giving milk or oils.
- Avoid giving alcohol.
- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.

- Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology].

Treat symptomatically.

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered

continued...

ALTDORF GLACIER 424

Chemwatch Material Safety Data Sheet

Issue Date: 01 Sept 2021 CHEMWATCH 16-3657

NC317ECP Version No:2.0

CD 2008/2 Page 3 of 11

Section 4 - FIRST AID MEASURES

necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

- Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing

skin disorders may be aggravated by exposure to this product.

- In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.

- High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

NOTE: Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.

- Foam.

- Dry chemical powder.

- BCF (where regulations permit).

- Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.

- Wear full body protective clothing with breathing apparatus.

- Prevent, by any means available, spillage from entering drains or water course.

- Use water delivered as a fine spray to control fire and cool adjacent area.

- Avoid spraying water onto liquid pools.

- DO NOT approach containers suspected to be hot.

- Cool fire exposed containers with water spray from a protected location.

- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Combustible.

- Slight fire hazard when exposed to heat or flame.

- Heating may cause expansion or decomposition leading to violent rupture of containers.

- On combustion, may emit toxic fumes of carbon monoxide (CO).

- May emit acrid smoke.

- Mists containing combustible materials may be explosive.

Combustion products include: carbon dioxide (CO₂), phosphorus oxides (PO_x), sulphur oxides (SO_x), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM: None

continued...

ALTDORF GLACIER 424

Chemwatch Material Safety Data Sheet

Issue Date: 01 Sept 2021 CHEMWATCH 16-3657

NC317ECP Version No:2.0

CD 2008/2 Page 4 of 11

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

Slippery when spilt.

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

Chemical Class: aliphatic hydrocarbons

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE RANK APPLICATION COLLECTION LIMITATIONS

LAND SPILL - SMALL

cross- linked 1 shovel R, W, SS

polymer -

particulate

cross- linked 1 throw pitchfork R, DGC, RT

polymer - pillow

wood fibre - 2 throw pitchfork R, P, DGC, RT

pillow

treated wood 2 throw pitchfork DGC, RT

fibre- pillow

sorbent clay - 3 shovel R, I, P

particulate

foamed glass - 3 throw pitchfork R, P, DGC, RT

pillow

LAND SPILL - MEDIUM

cross- linked 1 blower skiploader R, W, SS

polymer -

particulate

cross- linked 2 throw skiploader R, DGC, RT

polymer - pillow

sorbent clay - 3 blower skiploader R, I, P

particulate

polypropylene - 3 blower skiploader W, SS, DGC

particulate

expanded mineral 4 blower skiploader R, I, W, P, DGC

- particulate

polypropylene - 4 throw skiploader DGC, RT

continued...

ALTDORF GLACIER 424

Chemwatch Material Safety Data Sheet

Issue Date: 01 Sept 2021 CHEMWATCH 16-3657

NC317ECP Version No:2.0

CD 2008/2 Page 5 of 11

Section 6 - ACCIDENTAL RELEASE MEASURES

mat

Legend

DGC: Not effective where ground cover is dense

R; Not reusable

I: Not incinerable

P: Effectiveness reduced when rainy

RT: Not effective where terrain is rugged

SS: Not for use within environmentally sensitive sites

W: Effectiveness reduced when windy

Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;

R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988.

Slippery when spilt.

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/sec until

fill pipe submerged to twice its diameter, then ≤ 7 m/sec).

- Avoid splash filling.
- Do NOT use compressed air for filling discharging or handling operations.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.

continued...

ALTDORF GLACIER 424

Chemwatch Material Safety Data Sheet

Issue Date: 01 Sept 2021 CHEMWATCH 16-3657

NC317ECP Version No:2.0

CD 2008/2 Page 6 of 11

Section 7 - HANDLING AND STORAGE

- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

CARE: Water in contact with heated material may cause foaming or a steam explosion with possible severe burns from

wide scattering of hot material. Resultant overflow of containers may result in fire.

- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

+ + + + X +

+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- paraffinic distillate, heavy, solvent- dewaxed (severe): CAS:64742- 65- 0

MATERIAL DATA

Not available. Refer to individual constituents.

INGREDIENT DATA

PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE):

NOTE L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346. European Union (EU)

List of Dangerous Substances (Annex I) - up to the 29th ATP.

ES TWA: 5 mg/m³ refined mineral oil mist.

Human exposure to oil mist alone has not been demonstrated to cause health effects except at levels above 5 mg/m³ (this applies to particulates sampled by a method that does not collect vapour). It is not advisable to apply this standard to oils containing unknown concentrations and types of additive.

continued...

ALTDORF GLACIER 424

Chemwatch Material Safety Data Sheet

Issue Date: 01 Sept 2021 CHEMWATCH 16-3657

NC317ECP Version No:2.0

CD 2008/2 Page 7 of 11

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
 - chemical resistance of glove material,
 - glove thickness and
 - dexterity,
- are important in the selection of gloves.
- Wear chemical protective gloves, e.g. PVC.
 - Wear safety footwear or safety gumboots, e.g. Rubber.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level Maximum Protection Half- face Respirator Full- Face Respirator
ppm (volume) Factor

1000 10 A- AUS P -

1000 50 - A- AUS P

5000 50 Airline * -

5000 100 - A- 2 P

10000 100 - A- 3 P

100+ Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific

continued...

ALTDORF GLACIER 424

Chemwatch Material Safety Data Sheet

Issue Date: 01 Sept 2021 CHEMWATCH 16-3657

NC317ECP Version No:2.0

CD 2008/2 Page 8 of 11

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Dark oily liquid with a mild odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.

Mixes with water.

Molecular Weight: Not Applicable Boiling Range (°C): Not Available

Melting Range (°C): Not Available Specific Gravity (water= 1): 0.91

Solubility in water (g/L): Miscible pH (as supplied): Not Available

pH (1% solution): Not Available Vapour Pressure (kPa): Not Applicable

Volatile Component (%vol): Not Applicable Evaporation Rate: Not Applicable

Relative Vapour Density (air=1): Not Flash Point (°C): Not Applicable

Applicable

Lower Explosive Limit (%): Not Applicable Upper Explosive Limit (%): Not Applicable

Autoignition Temp (°C): Not Applicable Decomposition Temp (°C): Not Applicable

State: Liquid Viscosity: Not Applicable

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be damaging to the health of the individual.

EYE

There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

SKIN

The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant

continued...

ALTDORF GLACIER 424

Chemwatch Material Safety Data Sheet

Issue Date: 01 Sept 2021 CHEMWATCH 16-3657

NC317ECP Version No:2.0

CD 2008/2 Page 9 of 11

Section 11 - TOXICOLOGICAL INFORMATION

dermatitis as described in EC Directives.

The material may accentuate any pre-existing dermatitis condition.

Open cuts, abraded or irritated skin should not be exposed to this material.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Inhalation hazard is increased at higher temperatures.

CHRONIC HEALTH EFFECTS

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

Substance accumulation, in the human body, may occur and may cause some concern following repeated

or long-term occupational exposure.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE):

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

No data of toxicological significance identified in literature search.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

MATERIAL CARCINOGEN REPROTOXIN SENSITISER SKIN

paraffinic IARC:3
distillate,
heavy, solventdewaxed
(severe)

CARCINOGEN

IARC: International Agency for Research on Cancer (IARC) Carcinogens: paraffinic distillate, heavy, solvent-dewaxed (severe) Category: The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.

Section 12 - ECOLOGICAL INFORMATION

The lower molecular weight hydrocarbons are expected to form a "slick" on the surface of waters after release in calm sea conditions. This is expected to evaporate and enter the atmosphere where it will be degraded through reaction with hydroxy radicals.

Some of the material will become associated with benthic sediments, and it is likely to be spread over a fairly wide area of sea floor. Marine sediments may be either aerobic or anaerobic. The material, in probability, is biodegradable, under aerobic conditions (isomerised olefins and alkenes show variable results). Evidence also suggests that the hydrocarbons may be degradable under anaerobic conditions although such degradation in benthic sediments may be a relatively slow process.

Under aerobic conditions the material will degrade to water and carbon dioxide, while

continued...

ALTDORF GLACIER 424

Chemwatch Material Safety Data Sheet

Issue Date: 01 Sept 2021 CHEMWATCH 16-3657

NC317ECP Version No:2.0

CD 2008/2 Page 10 of 11

Section 12 - ECOLOGICAL INFORMATION

under anaerobic processes it will produce water, methane and carbon dioxide.

Based on test results, as well as theoretical considerations, the potential for bioaccumulation may be high. Toxic effects are often observed in species such as blue mussel, daphnia, freshwater green algae, marine copepods and amphipods.

Drinking Water Standards: hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE):

DO NOT discharge into sewer or waterways.

Section 13 - DISPOSAL CONSIDERATIONS

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction,
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: None

REGULATIONS

Soluble Cutting Oil EP (CAS: None):

No regulations applicable

paraffinic distillate, heavy, solvent-dewaxed (severe) (CAS: 64742-65-0) is found on the following regulatory lists;

Australia Hazardous Substances

Australia High Volume Industrial Chemical List (HVICL)

continued...

ALTDORF GLACIER 424

Chemwatch Material Safety Data Sheet

Issue Date: 01 Sept 2021 CHEMWATCH 16-3657

NC317ECP Version No:2.0

CD 2008/2 Page 11 of 11

Section 15 - REGULATORY INFORMATION

Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) Carcinogens

OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or

criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission

from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 01 Sept 2021

Print Date: 01 Sept 2021

LABEL FILE:

ALTDORF GLACIER 424 110mm x 75mm Label file for decanted product on following page:



GLACIER 424

GENERAL PURPOSE CUTTING FLUID

- Mineral based
- Suits most applications
- Inhibits rust & corrosion
- High lubricity
- Anti microbial



Distributed by
 **WOLFMACH**
0508 124 125